

30W Single Output Switching Power Supply

ELN-30 series



- Features :
- Universal AC input / Full range
- Protections: Short circuit / Over current / Over voltage
- Cooling by free air convection
- Built-in constant current limiting circuit with adjustable OCP level
- Optional dimming function : 1.1~10VDC (D type) or PWM (P type) controlled
- Fully isolated plastic case with IP64 level
- Class II power unit, no FG
- Class 2 power unit
- Pass LPS
- Suitable for LED lighting and moving sign applications (Note.8)
- 100% full load burn-in test
- Low cost
- 2 years warranty

SPECIFICATION

MODEL		ELN-30-5	ELN-30-9	ELN-30-12	ELN-30-15	ELN-30-24	ELN-30-27	ELN-30-48
	DC VOLTAGE	5V	9V	12V	15V	24V	27V	48V
OUTPUT	LED OPERATION VOLTAGE Note.7	3 ~ 5V	3~9V	3 ~ 12V	3~15V	3~24V	3~27V	3~48V
	RATED CURRENT	5A	3.4A	2.5A	2A	1.25A	1.12A	0.63A
	CURRENT RANGE	0~5A	0~3.4A	0~2.5A	0~2A	0~1.25A	0~1.12A	0~0.63A
	RATED POWER	25W	30.6W	30W	30W	30W	30.24W	30.24W
	RIPPLE & NOISE (max.) Note.2	80mVp-p	100mVp-p	120mVp-p	120mVp-p	150mVp-p	150mVp-p	250mVp-p
	VOLTAGE ADJ. RANGE	4.5 ~ 5.5V	8.7 ~ 10.5V	10.8 ~ 13.2V	13.5 ~ 16.5V	21.6~26.4V	24.3 ~ 29.7V	43.2 ~ 52.8V
		Can be adjusted by internal potentiometer SVR1						
	CURRENT ADJ. RANGE	-25% ~ 3%. Can be adjusted by internal potentiometer SVR2						
	VOLTAGE TOLERANCE Note.3	±5.0%						
	LINE REGULATION	±1.0%						
	LOAD REGULATION	±2.0%						
	SETUP, RISE TIME Note.6	500ms, 80ms / 230VAC 1000ms, 80ms / 115VAC at full load						
	HOLD UP TIME (Typ.)	50ms/230VAC 16ms/115VAC at full load						
INPUT		90 ~ 264VAC 127 ~ 370VDC						
	FREQUENCY RANGE	47 ~ 63Hz						
	EFFICIENCY (Typ.)	75%	80%	82%	82%	85%	85%	87%
	AC CURRENT (Typ.)	0.75A/115VAC		1 / -				1
	INRUSH CURRENT (Typ.)	COLD START 55A(twidth=465us measured at 50% Ipeak) at 230VAC						
	MAX. No. of PSUs on 16A CIRCUIT BREAKER	4 units (circuit breaker of type B) / 8 units (circuit breaker of type C) at 230VAC						
	LEAKAGE CURRENT	0.25mA/240VAC						
PROTECTION		95 ~ 110%						
	OVER CURRENT	Protection type : Constant current limiting, recovers automatically after fault condition is removed						
	OVER VOLTAGE	5.75 ~ 6.75V	11 ~ 13.5V	13.8 ~ 16V	17.5 ~ 21V	28 ~ 32V	31 ~ 36.4V	54 ~ 60V
						20 021	01 00.47	04 000
UNCTION	DIMMING CONTROL (OPTIONAL)	Protection type : Shut down o/p voltage, re-power on to recover 1.1 ~ 10VDC or PWM signal : 100Hz ~ 3KHz						
	WORKING TEMP.	-20 ~ +60°C (Refer to "Derating Curve")						
ENVIRONMENT		20 ~ 90% RH non-condensing						
	WORKING HUMIDITY	· · · · · · · · · · · · · · · · · · ·						
	STORAGE TEMP., HUMIDITY	-40 ~ +80°C, 10 ~ 95% RH						
	TEMP. COEFFICIENT	±0.03%/°C (0 ~ 50°C)						
	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes						
	SAFETY STANDARDS	UL1310, CAN/CSA C22.2 No. 223-M91(except for 48V), IP64 approved ; design refer to TUV EN60950-1						
SAFETY &	WITHSTAND VOLTAGE	I/P-O/P:3KVAC						
EMC	ISOLATION RESISTANCE	I/P-O/P:>100M Ohms / 500VDC / 25°C/ 70% RH						
	EMC EMISSION	Compliance to EN55022 (CISPR22) Class B, EN61000-3-2 Class A, EN61000-3-3						
	EMC IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,8,11, EN55024, light industry level, criteria A						
OTHERS	MTBF	628.3Khrs min.	MIL-HDBK-217	F (25°C)				
	DIMENSION	145*47*30mm (L	,					
	PACKING	0.26Kg; 60pcs/16						
NOTE	 Ripple & noise are measure Tolerance : includes set up Derating may be needed ui The power supply is consid complete installation, the fir Length of set up time is me Constant current operation 	ally mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. red at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. to tolerance, line regulation and load regulation. Inder low input voltage. Please check the static characteristics for more details. dered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the nal equipment manufacturers must re-qualify EMC Directive on the complete installation again. easured at first cold start. Turning ON/OFF the power supply may lead to increase of the set up time. region is within the specified output voltage range above. This is the suitable operation region for LED related applications. ble for lighting applications in EU countries. Please check with your local authorities for the possible use of the unit.						



30W Single Output Switching Power Supply

ELN-30 series



File Name:ELN-30-SPEC 2015-05-28



ELN-30 series

Dimming Control (Optional)

Level of output current can be adjusted through the dimming control function. When there is no signal sending to the control wires (open circuit between the two control wires), the power supply unit will operate as 0V (D-type) or 0% duty (P-type) of input signal and hence the output current will be zero.

(1)1.1~10V (D type, & : ELN-30-12D)





(2)PWM (P type, & : ELN-30-12P)



Lo:0V Hi:10V

